



Retail Price List 2025

THE FIRST POWER AMPLIFIER



Nominal Output Power:
330 watts RMS @ 8 ohms
660 watts RMS @ 4 ohms
1320 watts RMS @ 2 ohms

A/B Class

Analog Input:

2 x XLR > 47 kohms
2 x XLR bypass output

Gain:

32 dB for maximal out

Speaker Output Impedance:

< 0.2 ohms from 10 Hz to 40 kHz
(measured in 8 ohms)

Frequency Response:

1.0 Hz - 300 kHz, $\pm 0,1$ dB

Slew Rate:

> 1300 V/ μ s

DC Output Voltage:

± 15 mV

Total Harmonic Distortion (THD):

< 0,01 % from 5 Hz to 100 kHz

Signal to noise ratio:

> 116 dB (A) @ nominal power

Power consumption:

2,5 watts Standby, 40 watts @ idle,
2500 watts @ maximum output power

Size in mm:

440 x 447 x 216 (WxDxH)

Size in Inchs:

17,33 x 17,60 x 8,5 (WxDxH)

Net Weight:

45 Kg

Fuse ratings:

115 volts: 20A (T)

230 volts: 10A (T)

Factory selectable

€ 40.000,00

THE DRIVER PREAMPLIFIER



Line Gain:

Up to + 10 dB

Analog Input Impedances:

4 x RCA line 47 kohms,

from 5 Hz to 100 kHz

4 x XLR Line 47 kohms,

from 5 Hz to 100 kHz

1 x optional future input slot

Line Output impedances:

RCA 30 ohms

XLR 600 ohms

REC OUT < 100 ohms

Frequency Response:

1 Hz - 300 kHz, $\pm 0,2$ dB

Rise Time:

< 0.8 μ s

Slew Rate:

> 34 V/ μ s

Total Harmonic Distortion (THD):

< 0,00001 % from 10 Hz to 100 kHz
max out + 18 dBu

Crosstalk:

< - 90 dB from 20Hz to 20kHz

Signal to noise ratio:

> 120 dB (A)

Power consumption:

5 - 60 watts depending on
working conditions

Remote control:

full functions

Size in mm:

440 x 335 x 136 (WxDxH)

Size in inches:

17,33 x 13,19 x 5,35 (WxDxH)

Net weight:

15 Kg

Fuse ratings:

115 volts: 2A (T)

230 volts: 1A (T)

Factory selectable

€ 25.000,00